

Amendments to the Specification:

Page 4, replace paragraph [0019] with the following amended paragraph:

[0019] ~~Figure 7 shows~~ Figures 7a-7d show in four models the utilization of the cleaning head holder together with a cleaning head dispenser.

Page 9, replace paragraph [0039] with the following amended paragraph:

[0039] The cleaning head section 56 houses a cleaning head 58 located adjacent or proximate an end 57 of the body 51. The cleaning head 58 may comprises a cleaning means 60, such as the embodiments described below with reference to ~~Figures 12a and 12b~~ Figure 14. The cleaning means 60 may comprise bristles, fibers, cotton and/or paper masses, unitary cloth, and/or various other materials or arrangements.

Page 15, replace paragraph [0061] with the following amended paragraph:

[0061] Referring to Figures 16a-c, illustrated are sectional views an alternative handle 170 (a portion of which is shown) constructed according to aspects of the present disclosure. ~~The handle 70~~ handle 170 includes a cleaning head section 172 for housing a plunger head 174. A cleaning head 176 associated with the handle 170 includes a sleeve 178, a portion of which is positioned around a plurality of bristles 180 to define a recessed portion 182. As shown more particularly in Figure 16a, the cleaning head 176 may be adapted for a friction fit or interference fit with the plunger head 174 when the plunger head is in an initial position.

Page 18, replace paragraph [0070] with the following amended paragraph:

[0070] The cleaning kit 900 may also include a hanging clip 940 configured to interface with a toilet, such that the handle 930 may be hung from the toilet via the hanging clip 940. For example, the clip 940 may include a first hook 945 configured to fit between the top edge of a toilet tank and the lid of the toilet tank, and a second hook 947 configured to fit into an opening in the ~~handle 935~~ handle 930. Accordingly, the handle 930 may be conveniently stored with the toilet, eliminating the storage hassle experienced with conventional toilet brushes.